FLOS

KTribe Floor 1



KTribe Floor 1 by Philippe Starck , 2007	
Item Code	F62650
Mounting	Floor
Environment	Indoor
Finish	Aluminized bronze, Aluminized silver, Fabric, Fumée, Transparent
Weight	4.3kg.

Technical description



Floor lamp providing diffused lighting; a switch located near the diffuser allows for 4-level light adjustment via a "remote dimmer positioned on the power cord near the plug. Base and rod support in die-cast, polished and chrome-plated Zamak alloy. Rod, arm support, arm and diffuser support in polished aluminum tube. Molded steel counterweight with galvanized finish. Injectionmolded PC (polycarbonate) inner diffuser opal color. Outer diffusers in transparent or fumèe PMMA (polymethylmethacrylate) and silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent, or transparent brown for the outer bronze diffuser.



Electrical

Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the step regulation of light brightness with a push button hidden under the diffuser stem.
Voltage	230
Battery	No

Supply included

Physical

Cord Length (Mm)	1500
Construction Material	Aluminum, Fabric, Polycarbonate, Polymethylmethacrylate
Weight (Kg)	4.3

Certificate



FLOS



KTribe Floor 2



KTribe Floor 2

by Philippe Starck , 2006

Item Code	F63050
Mounting	Floor
Environment	Indoor
Finish	Aluminized bronze, Aluminized silver, Fabric, Fumée, Transparent
Weight	6.7kg.

Technical description



Floor lamp providing diffused lighting. Base, rod support and diffuser support in die-cast, polished and chrome-plated Zamak alloy. Galvanized P04 steel base cover. Injectionmolded PC (polycarbonate) opal inner diffuser and support for the lamp-holder. Outer diffusers in transparent or fumèe PMMA (polymethylmethacrylate), and silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent or transparent diffuser and silver diffuser) or transparent brown for the outer bronze diffuser. On the cable there is the electronic dimmer which allows the regulation of light brightness.



Electrical

Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220/240
Battery	No

Supply included

Physical

Cord Length (Mm)	2010
Construction Material	Aluminum, Fabric, Polycarbonate, Polymethylmethacrylate

Weight (Kg)

6.7

Certificate



FLOS



KTribe Floor 3



KTribe Floor 3 by Philippe Starck , 2007

Item Code	F63010
Mounting	Floor
Environment	Indoor
Finish	Aluminized bronze, Aluminized silver, Fabric, Fumée, Transparent
Weight	14kg.

Technical description



Floor lamp providing diffused lighting. Base, rod support and diffuser support in die-cast, polished and chrome-plated Zamak alloy. Galvanized P04 steel base cover. Injectionmolded PC (polycarbonate) opal inner diffuser and support for the lamp-holder. Outer diffusers in transparent or fumèe PMMA (polymethylmethacrylate), and silver or bronze on the inner surface, by vacuum aluminum coating. Injection-molded PC (polycarbonate) upper ring, completely transparent or transparent diffuser and silver diffuser) or transparent brown for the outer bronze diffuser. On the cable there is the electronic dimmer which allows the regulation of light brightness.



Electrical

Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Voltage	220/240
Battery	No

Supply included

Physical

Construction Material	Aluminum, Fabric, Polycarbonate, Polymethylmethacrylate
Weight (Kg)	14

Certificate

