LIGHT SHADOW FIXED NO TRIM DALI VERSION 4 SPOTS OPTIC FLOOD

Mounting Ceiling recessed

Lamps descriptionPower LED 10,8W 1120 lm 3000K CRI 90Luminaire luminous fluxExtreme Cut-off. See reference number

Environment Indoo

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Fixed
Light distribution symmetry Symmetric
Beam angle 33° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable DALI

Emergency Without Insulation class Class II

PHYSICAL

Length (mm) 140
Recessed depth (mm) 75
Weight (kg) 0,34






Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9235.40.DA - 841lm	White / White
	Black / White
03.9237.40.DA - 860lm	White / Chrome
03.9237.14.DA - 860lm	Black / Chrome
03.9238.40.DA - 833lm	White / Matt Gold
03.9238.14.DA - 833lm	Black / Matt Gold
● 03.9236.40.DA - 817lm	White / Black
03.9236.14.DA - 817lm	Black / Black




















Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood . Accessories

Mounting





08.0511.00

08.0052.90

Pre-installation frame. Fixed No Trim 4L

Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood . Lamps



Power LED

Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED




Light Shadow Fixed No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9235.40.DA - 841lm	White / White
03.9235.14.DA - 841Im	Black / White
03.9237.40.DA - 860lm	White / Chrome
03.9237.14.DA - 860lm	Black / Chrome
03.9238.40.DA - 833lm	White / Matt Gold
03.9238.14.DA - 833lm	Black / Matt Gold
3.9236.40.DA - 817lm	White / Black
03.9236.14.DA - 817lm	Black / Black




















LIGHT SHADOW ADJUSTABLE NO TRIM DALI VERSION 4 SPOTS OPTIC FLOOD

Mounting Ceiling recessed

 Lamps description
 Power LED 10,8W 1120 Im 3000K CRI 90

 Luminaire luminous flux
 Extreme Cut-off. See reference number

Environment Indoo

Notes It requires an pre-installation frame, to be ordered separately.

OPTICAL

Aiming Adjustable
Light distribution symmetry Symmetric
Beam angle 33° Flood

ELECTRICAL

Transformer availability Included
Transformer mounting Remote

Transformer type Electronic dimmable DALI

EmergencyWithoutInsulation classClass II

PHYSICAL

Recessed depth (mm) 75 Weight (kg) 0,34






Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9435.40.DA - 841Im White / White 03.9435.14.DA - 841lm Black / White 03.9437.40.DA - 860lm White / Chrome 03.9437.14.DA - 860lm Black / Chrome White / Matt Gold → 03.9438.40.DA - 833lm 03.9438.14.DA - 833lm Black / Matt Gold 03.9436.40.DA - 817lm White / Black 03.9436.14.DA - 817lm Black / Black






















Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood . Accessories

Mounting





08.0516.00

08.0059.90

Pre-installation frame. Adjustable No Trim 4L Accessory for mounting of No Trim continuous line

Accessory for mounting of No Trim continuous line. Each accessory allows connection between two No Trim preinstallation frames.

Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood . Lamps



Power LED Lamp category:

LED

Socket:

Special base

Lamp type:

Power LED



Light Shadow Adjustable No Trim Dali Version 4 Spots Optic Flood

designed by FLOS Architectural

Recessed integrated luminaire with 4 LED lighting spots. Remote power supply included.

03.9435.40.DA - 841lm	White / White
03.9435.14.DA - 841lm	Black / White
03.9437.40.DA - 860lm	White / Chrome
03.9437.14.DA - 860lm	Black / Chrome
03.9438.40.DA - 833lm	White / Matt Gold
03.9438.14.DA - 833lm	Black / Matt Gold
3.9436.40.DA - 817lm	White / Black
03.9436.14.DA - 817lm	Black / Black

