

Arrangements Line

by Michael Anastassiades , 2018


Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|---|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.7 Kg |
| Light sources available | 1 x FLEX STRIP LED 29W 1480lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 29W |
| Battery | No |
| Supply included | No |

| | |
|-------------|----------|
| Cord Length | 2500 mm |
| Materials | Aluminum |

| | |
|--------|--------------------|
| Colors | ● F0401030 - Black |
|--------|--------------------|

| | |
|-------------|--|
| Certificate |    |
|-------------|--|




Arrangements Line


by Michael Anastassiades , 2018




F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Round Small

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.5 Kg |
| Light sources available | 1 x FLEX STRIP LED 21W 1068lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 21W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0406030 - Black |
| Certificate |    |

Arrangements Round Small


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Round Medium

by Michael Anastassiades , 2018


Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.


Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.8 Kg |
| Light sources available | 1 x FLEX STRIP LED 35W 1770lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 35W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0407030 - Black |
| Certificate |    |

Arrangements Round Medium


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Round Large

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 1.3 Kg |
| Light sources available | 1 x FLEX STRIP LED 54W 2751lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 54W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0408030 - Black |
| Certificate |    |

Arrangements Round Large


by Michael Anastassiades , 2018




F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Square Small

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.




Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.5 Kg |
| Light sources available | 1 x FLEX STRIP LED 20W 883lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 20W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0410030 - Black |
| Certificate |    |

Arrangements Square Small


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Drop Up

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.


Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.5 Kg |
| Light sources available | 1 x FLEX STRIP LED 30W 1530lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 32W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0414030 - Black |
| Certificate |    |

Arrangements Drop Up


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Drop Down

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.5 Kg |
| Light sources available | 1 x FLEX STRIP LED 30W 1530lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 30W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0413030 - Black |
| Certificate |    |

Arrangements Drop Down


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Broken Line

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.


Cable length 2.5m




| | |
|-------------------------|---|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.65 Kg |
| Light sources available | 1 x FLEX STRIP LED 24W 1200lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 24W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0405030 - Black |
| Certificate | <div> <div>CE</div> <div>IP20</div> <div>III</div> </div> |

Arrangements Broken Line


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W



Arrangements Square Large

by Michael Anastassiades , 2018



Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.

The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m




| | |
|-------------------------|--|
| Mounting | Pendant |
| Environment | Indoor |
| Finish | Black |
| Weight | 0.7 Kg |
| Light sources available | 1 x FLEX STRIP LED 34W 1657lm 2700K CRI90 [i] |
| Emergency | Without |
| Voltage | 48V |
| Power | 34W |
| Battery | No |
| Supply included | No |
| Cord Length | 2500 mm |
| Materials | Aluminum |
| Colors | ● F0409030 - Black |
| Certificate |    |

Arrangements Square Large


by Michael Anastassiades , 2018



F0415030
Big Rose-MAX190W



F0416030
Small Rose-MAX70



F0418030
Recessed Rose-MAX190W