





## Glo-Ball Suspension 1

by Jasper Morrison , 1998

Suspension lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Gloss white painted pressed steel diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.



Mounting	Pendant
Environment	Indoor
Finish	White
Weight	2.7 Kg
Light sources available	1 x MAX 150W E27 HSGS 2870lm 2900K [e] cod. RF20358 DIMMER 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 DIMMER 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 DIMMER 1 x LED 17W E27 2000lm 2700K [e] cod. RF26259 DIMMER 0 x LED 17W E27 2000lm 3000K [e] cod. RF26258 DIMMER

Emergency	Without
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes

Cord Length	3700 mm
Materials	Blown glass, Steel

Colors	● F3005061 - White
--------	--------------------

Certificate	
-------------	--



## Glo-Ball Suspension 2

by Jasper Morrison , 1998

Suspension lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.






Mounting	Pendant
Environment	Indoor
Finish	White
Weight	5.6 Kg
Light sources available	1 x HSGS E27 205W 3000K Halolux Ceram.Eco 4200lm - RF19973 1 x LED E27 21W 3000K 2452lm A65 - RF26998 - DIMM.

Emergency	Without
Voltage	220-240V
Power	MAX 250W
Battery	No
Supply included	Yes

Cord Length	3700 mm
Materials	Blown glass, Steel

Colors	F3010061 - White
--------	------------------

Certificate	    
-------------	--






## Glo-Ball Suspension 2 Eco

by Jasper Morrison , 1998

Suspension lamp providing diffused light. Diffuser consisting of an externally acid-etched, hand blown, flashed opaline glass. Transparent, injection molded polycarbonate diffuser support. 30% fiberglass reinforced injection-molded polyamide rose; pressed and galvanized ceiling fitting. Steel suspension cable.



Mounting	Pendant
Environment	Indoor
Finish	White
Weight	5.6 Kg
Light sources available	1 x FSMH Gx24q-4 42W 31-830 3000K 3200lm - RF14594
Emergency	Without
Voltage	220-240V
Power	42W
Battery	No
Supply included	Yes
Cord Length	3700 mm
Materials	Blown glass, Steel
Colors	 F3011061 - White
Certificate	    