





F014A30K030 - Black

Lighting unit with diffuse light for exterior ground/wall installation. Opalescent diffuser in shiny white translucent blown glass.

The structure is made of stainless steel for effective resistance to atmospheric agents. The body is painted an opaque black. The corner lamp can be positioned in two directions, either vertically or horizontally. The light comes complete with external system to adjust the amount of light. LED light source included. 5-metre outdoor cable with Schuko IP44 plug. Backlit IP65 pedal dimmer switch on the cable for easy ON/OFF and to adjust the amount of light.


CASAMBI function on demand.

Main specifications

Lamp category	LED	Mountings	Wall
Power	9	Environment	Outdoor
CCT	3000K		
CRI	80		
Net lumen (lm)	423		


Optical

Lighting typeDirectLED typePower LEDLight distributionSymmetricOptical typeDiffused light



Luminous flux luminaire 423 lm

Beam	Beam Angle:		
h(m)	E(lx)	D(m	
1	2		
2	4		
3	9		
4	35		
5	0		



Certification / Marking

\F/	I P	IK	(
💟	65	04	100

Electrical

Frequency (Hz)50-60Driver typeDimmer on boardVoltage (V)100-240EmergencyWithoutLamp holderLEDInsulation classIIDimmableYesDriverremote included

Physical

ColorBlackOrientationFixedWeight (kg)2.1