## FLOS



## Skygarden 1

by Marcel Wanders , 2007

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy, liquid-painted white. Molded upper bushing in die-cast, polished aluminum alloy, protected with transparent paint on the entire visible part. Upper cable gland and blocking ring nut in black injectionmolded PC (polycarbonate). Shaped, galvanized adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lamp holder and fixing support in black injection-molded PPS (polyphenylene sulfide). Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Skygarden 1 frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment Gray, injection-molded PA6 (Nylon) rose.





Mounting	Pendant
Environment	Indoor
Weight	13.0 Kg
Light sources available	1 x LED 15W E27 1515lm 3000K [e] cod. RF28367 Non dimmable
Emergency	Without
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes
Cord Length	4000 mm
Materials	Glass, Plaster, Stainless steel
Colors	<ul> <li>F0001031 - Black</li> <li>F0001044 - Gold</li> <li>F0001047 - Rusty Brown</li> <li>F0001030 - Glosy Black</li> <li>F0001009 - Glossy White</li> </ul>
Certificate	

## FLOS

## **Technical Specifications**




Skygarden 2

by Marcel Wanders , 2007

Suspension luminaire providing diffused lighting. Hemispherical, mechanically-processed cast plaster diffuser, painted white inside. Outer finish: rust, glossy black, glossy white or matte gold. Plaster diffuser support in die-cast aluminum alloy. Upper cable gland and blocking ring nut in black injection-molded PC. Shaped, adjustment screws. Transparent, injection-molded, upper and lower silicone shock absorbers. Lampholder and fixing support in PPS. Flashed and blown opal glass diffuser. Molded fixing ring nut in die-cast aluminum alloy with alodine plating. Frieze in photo-etched and mechanically drawn AISI 304 steel. Molded and galvanized steel ceiling attachment. Gray, injectionmolded PC rose, painted the same color as the body.

	1.1
A second	1 - Areas
and the pr	
	1
111-30 M	ALC: NO
Mar Land	- martin



Mounting	Pendant
Environment	Indoor
Weight	29,0 Kg
Light sources available	1 x LED 15W E27 1515lm 3000K [e] cod. RF28367 Non dimmable 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 Dimmable 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 Dimmable
Emergency	Without
Voltage	220-250V
Power	MAX 230W
Battery	No
Supply included	Yes
Cord Length	4000 mm
Materials	Glass, Plaster, Stainless steel
Colors	<ul> <li>F0002031 - Black</li> <li>F0002044 - Gold</li> <li>F0002047 - Rusty Brown</li> <li>F0002030 - Glosy Black</li> <li>F0002009 - Glossy White</li> </ul>
Certificate	$C E \mathfrak{C} E E E E \mathfrak{E} E E E E E E E \mathsf$